

*Always verify tips or orifices you received are the size which you require before using with chemical. Chemical rates need to be obtained from your chemical dealer.

ConeJet® VisiFlo® Hollow Cone Spray Tips



Excellent: Post-Emerge Contact Herbicides, Fungicides and Insecticides - To assure finely atomized spray droplets reach target areas.
Good: For use with defoliants and foliar fertilizers at pressures 40 PSI and above.

Features:


- VisiFlo color-coded version consists of stainless steel or ceramic orifice in polypropylene body.
- Maximum operating pressure 300 PSI.
- Spray angle is 80° at 100 PSI.
- Ideal for banding with two or three nozzles over the row.
- Finely atomized spray pattern provides thorough coverage.

CONEJET	
PART NO.	LIST PRICE
TX-# (Brass).....	\$7.83
TX-VS#.....	\$8.75
TX-SS#.....	\$49.05
## - Specify Tip Size	
VS - Stainless Steel w/ VisiFlo® Color Coding	
SS - Stainless Steel	
REQUIRED CAP	
114445A*-CELRL.....	\$1.58
replaces cap 25608-NYR	
* - Specify Cap Color	



How to order:

- Specify tip number.
 Examples:
 TX-VS4 - Stainless Steel with VisiFlo color-coding
 TX-4 - Brass
 TX-SS4 - Stainless Steel
 TX-VK4 - Ceramic with VisiFlo color-coding



Band Width	GPA CONVERSION FACTORS*	
	30°	30°
8"	3.75	
10"	3.00	
12"	2.50	
15"	2.00	



*To find GPA rate on band widths, multiply the tabulated GPA for ROW SPACING by the conversion factors.

Nozzle	PSI	CAPACITY TWO NOZZLES IN GPM	CAPACITY TWO NOZZLES IN OZ/MIN	GPA 30°					PSI	CAPACITY THREE NOZZLES IN GPM	CAPACITY THREE NOZZLES IN OZ/MIN	GPA 30°				
				3 MPH	4 MPH	5 MPH	6 MPH	7 MPH				3 MPH	4 MPH	5 MPH	6 MPH	7 MPH
				TX-1	40	0.033	4.2	2.2				1.6	1.3	1.1	0.93	40
TX-1 (100)	60	0.039	5.0	2.6	1.9	1.5	1.3	1.1	60	0.059	7.6	3.9	2.9	2.3	1.9	1.7
TX-2	75	0.043	5.5	2.8	2.1	1.7	1.4	1.2	75	0.065	8.3	4.3	3.2	2.6	2.1	1.8
TX-2 (100)	90	0.047	6.0	3.1	2.3	1.9	1.6	1.3	90	0.070	9.0	4.6	3.5	2.8	2.3	2.0
TX-3	120	0.053	6.8	3.5	2.6	2.1	1.7	1.5	120	0.079	10	5.2	3.9	3.1	2.6	2.2
TX-4	40	0.067	8.6	4.4	3.3	2.7	2.2	1.9	40	0.100	13	6.6	5.0	4.0	3.3	2.8
TX-4 (100)	60	0.080	10	5.3	4.0	3.2	2.6	2.3	60	0.12	15	7.9	5.9	4.8	4.0	3.4
TX-6	75	0.088	11	5.8	4.4	3.5	2.9	2.5	75	0.13	17	8.6	6.4	5.1	4.3	3.7
TX-6 (50)	90	0.095	12	6.3	4.7	3.8	3.1	2.7	90	0.14	18	9.2	6.9	5.5	4.6	4.0
TX-8	120	0.11	14	7.3	5.4	4.4	3.6	3.1	120	0.16	20	10.6	7.9	6.3	5.3	4.5
TX-10	40	0.10	13	6.6	5.0	4.0	3.3	2.8	40	0.15	19	9.9	7.4	5.9	5.0	4.2
TX-10 (100)	60	0.12	15	7.9	5.9	4.8	4.0	3.4	60	0.18	23	11.9	8.9	7.1	5.9	5.1
TX-12	75	0.13	17	8.6	6.4	5.1	4.3	3.7	75	0.20	26	13.2	9.9	7.9	6.6	5.7
TX-12 (50)	90	0.14	18	9.2	6.9	5.5	4.6	4.0	90	0.21	27	13.9	10.4	8.3	6.9	5.9
TX-18	120	0.16	20	10.6	7.9	6.3	5.3	4.5	120	0.24	31	15.8	11.9	9.5	7.9	6.8
TX-26	40	0.13	17	8.6	6.4	5.1	4.3	3.7	40	0.20	26	13.2	9.9	7.9	6.6	5.7
TX-26 (50)	60	0.16	20	10.6	7.9	6.3	5.3	4.5	60	0.24	31	15.8	11.9	9.5	7.9	6.8
TX-36	75	0.18	23	11.9	8.9	7.1	5.9	5.1	75	0.27	35	17.8	13.4	10.7	8.9	7.6
TX-48	90	0.19	24	12.5	9.4	7.5	6.3	5.4	90	0.29	37	19.1	14.4	11.5	9.6	8.2
TX-60	120	0.22	28	14.5	10.9	8.7	7.3	6.2	120	0.33	42	22	16.3	13.1	10.9	9.3
TX-84	40	0.20	26	13.2	9.9	7.9	6.6	5.7	40	0.30	38	19.8	14.9	11.9	9.9	8.5
TX-84 (50)	60	0.24	31	15.8	11.9	9.5	7.9	6.8	60	0.36	46	24	17.8	14.3	11.9	10.2
TX-108	75	0.27	35	17.8	13.4	10.7	8.9	7.6	75	0.40	51	26	19.8	15.8	13.2	11.3
TX-108 (50)	90	0.29	37	19.1	14.4	11.5	9.6	8.2	90	0.43	55	28	21	17.0	14.2	12.2
TX-144	120	0.33	42	22	16.3	13.1	10.9	9.3	120	0.50	64	33	25	19.8	16.5	14.1
TX-180	40	0.27	35	17.8	13.4	10.7	8.9	7.6	40	0.40	51	26	19.8	15.8	13.2	11.3
TX-180 (50)	60	0.32	41	21	15.8	12.7	10.6	9.1	60	0.49	63	32	24	19.4	16.2	13.9
TX-240	75	0.36	46	24	17.8	14.3	11.9	10.2	75	0.54	69	36	27	21	17.8	15.3
TX-300	90	0.39	50	26	19.3	15.4	12.9	11.0	90	0.59	76	39	29	23	19.5	16.7
TX-360	120	0.45	58	30	22	17.8	14.9	12.7	120	0.68	87	45	34	27	22	19.2
TX-480	40	0.33	42	22	16.3	13.1	10.9	9.3	40	0.50	64	33	25	19.8	16.5	14.1
TX-480 (50)	60	0.40	51	26	19.8	15.8	13.2	11.3	60	0.61	78	40	30	24	20	17.3
TX-600	75	0.45	58	30	22	17.8	14.9	12.7	75	0.68	87	45	34	27	22	19.2
TX-720	90	0.49	63	32	24	19.4	16.2	13.9	90	0.74	95	49	37	29	24	21
TX-900	120	0.56	72	37	28	22	18.5	15.8	120	0.85	109	56	42	34	28	24
TX-1080	40	0.40	51	26	19.8	15.8	13.2	11.3	40	0.60	77	40	30	24	19.8	17.0
TX-1080 (50)	60	0.49	63	32	24	19.4	16.2	13.9	60	0.73	93	48	36	29	24	21
TX-1440	75	0.54	69	36	27	21	17.8	15.3	75	0.81	104	53	40	32	27	23
TX-1800	90	0.59	76	39	29	23	19.5	16.7	90	0.88	113	58	44	35	29	25
TX-2160	120	0.68	87	45	34	27	22	19.2	120	1.01	129	67	50	40	33	29
TX-2880	40	0.60	77	40	30	24	19.8	17.0	40	0.90	115	59	45	36	30	25
TX-2880 (50)	60	0.73	93	48	36	29	24	21	60	1.10	141	73	54	44	36	31
TX-3600	75	0.82	105	54	41	32	27	23	75	1.23	157	81	61	49	41	35
TX-4320	90	0.90	115	59	45	36	30	25	90	1.35	173	89	67	53	45	38
TX-5040	120	1.03	132	68	51	41	34	29	120	1.55	198	102	77	61	51	44
TX-6480	40	0.87	111	57	43	34	29	25	40	1.30	166	86	64	51	43	37
TX-6480 (50)	60	1.06	136	70	52	42	35	30	60	1.59	204	105	79	63	52	45
TX-8160	75	1.18	151	78	58	47	39	33	75	1.78	228	117	88	70	59	50
TX-9840	90	1.30	166	86	64	51	43	37	90	1.94	248	128	96	77	64	55
TX-11760	120	1.49	191	98	74	59	49	42	120	2.24	287	148	111	89	74	63

Note: Always double check your application rates. Tabulations are based on spraying water at 70°F (21°C).