

*Always verify tips or orifices you received are the size which you require before using with chemical. Chemical rates need to be obtained from your chemical dealer.

Turbo TeeJet® Induction Flat Spray Tips

DICAMBA APPROVED
See page 49 for more information

Typical Applications:

Extremely coarse droplet size provides the best drift control possible and is ideal for soil applied and post-emerge systemic products, including dicamba.

Features:

- 110° wide angle, air induction, tapered flat spray tip pattern based on the patented outlet orifice design of the original Turbo TeeJet® nozzle.
- Patented orifice design provides large, round passages to minimize plugging.
- Depending on the chemical, produces large air-filled drops through a Venturi air aspirator resulting in less drift.
- All polymer construction for excellent chemical and wear resistance.
- Compact size to prevent tip damage.
- Removable pre-orifice.
- Ideal for use with automatic sprayer controllers.
- Wide operating pressure range: 15-100 PSI.
- Automatic spray alignment with 114443A*-CELR Quick TeeJet cap and gasket for capacities 015 thru 06.
- Automatic spray alignment with 114502A*-CELR Quick TeeJet cap and gasket for capacities 08 and 10.

PART NO.	LIST PRICE
SIZES 01-06	
TTI1100##-VP (01-06).....	\$14.97
TTI1100##-VP-C (01-06).....	\$17.03
REQUIRED CAP	
114443A*-CELR.....	\$1.58
replaces cap 25598-NYR	
SIZES 08-10	
TTI1100##-VP (08-10).....	\$17.49
TTI1100##-VP-CE (08-10).....	\$20.36
REQUIRED CAP	
114502A*-CELR.....	\$2.61
Available in Black, Light Blue, Telemagenta, Light Green & White	
*replaces cap 98579-1-NYR	



- Specify Tip Size - C / CE - Includes Quick
* - Specify Cap Color TeeJet Cap & Gasket

NEW QUICK TEEJET CAP

Dedicated to TTI Tips.


- Allows direct, straight-in spray tip placement.
- Simplifies assembly automation.




PART NO.	LIST PRICE
SIZES 01-06	
115835A*-CELR (01-06).....	\$1.58

NOZZLE	PSI	DROPS PER MIN	CAPACITY ONE NOZZLE IN GPM	CAPACITY ONE NOZZLE IN OZ./MIN.	GPA										GALLONS PER 1000 SQ. FT.			
					20"													
					4 MPH	5 MPH	6 MPH	8 MPH	10 MPH	12 MPH	15 MPH	20 MPH	2 MPH	3 MPH	4 MPH	5 MPH		
TTI110015 (100)	15 UC	0.092	12	6.8	5.5	4.6	3.4	2.7	1.8	1.4	0.31	0.21	0.16	0.13				
	20 UC	0.11	14	8.2	6.5	5.4	4.1	3.3	2.2	1.6	0.37	0.25	0.19	0.15				
	30 UC	0.13	17	9.7	7.7	6.4	4.8	3.9	3.2	2.6	1.9	0.44	0.29	0.22	0.18			
	40 UC	0.15	19	11.1	8.9	7.4	5.6	4.5	3.7	3.0	2.2	0.51	0.34	0.26	0.20			
	50 UC	0.17	22	12.6	10.1	8.4	6.3	5.0	4.2	3.4	2.5	0.58	0.39	0.29	0.23			
TTI11002 (50)	15 UC	0.18	23	13.4	10.7	8.9	6.7	5.3	4.5	3.6	2.7	0.61	0.41	0.31	0.24			
	20 UC	0.20	26	14.9	11.9	9.9	7.4	5.9	4.9	4.0	3.0	0.68	0.45	0.34	0.27			
	30 UC	0.22	28	16.3	13.1	10.9	8.2	6.5	5.4	4.4	3.3	0.75	0.50	0.37	0.30			
	40 UC	0.24	31	17.8	14.3	11.9	8.9	7.1	5.9	4.8	3.6	0.82	0.54	0.41	0.33			
	50 UC	0.26	33	19.3	15.4	12.9	9.7	7.7	6.4	5.1	3.9	0.88	0.58	0.44	0.35			
TTI110025 (50)	15 UC	0.28	36	21	16.6	13.9	10.4	8.3	6.9	5.5	4.2	0.95	0.63	0.48	0.38			
	20 UC	0.30	38	22	17.8	14.9	11.1	8.9	7.4	5.9	4.5	1.0	0.68	0.51	0.41			
	30 UC	0.32	41	24	19.0	15.8	11.9	9.5	7.8	6.3	4.8	1.1	0.73	0.54	0.44			
	40 UC	0.34	44	25	20.4	16.7	12.8	9.8	8.2	6.5	4.9	1.1	0.75	0.56	0.45			
	50 UC	0.35	45	26	21	17.3	13.0	10.4	8.7	6.9	5.2	1.2	0.79	0.60	0.48			
TTI11003 (50)	15 UC	0.38	49	28	23	18.8	14.1	11.3	9.2	7.5	5.6	1.2	0.86	0.65	0.52			
	20 UC	0.40	51	30	24	19.8	14.9	11.9	9.9	7.9	5.9	1.4	0.91	0.68	0.54			
	30 UC	0.42	54	31	25	21	15.6	12.5	10.4	8.3	6.2	1.4	0.95	0.71	0.57			
	40 UC	0.45	58	33	27	22	16.7	13.4	11.4	8.9	6.7	1.5	1.0	0.77	0.62			
	50 UC	0.47	60	35	28	23	17.4	14.0	11.6	9.3	7.0	1.6	1.1	0.80	0.64			
TTI11004 (50)	15 UC	0.48	61	36	29	18.3	14.5	11.9	9.9	7.9	5.9	1.6	1.1	0.83	0.67			
	20 UC	0.50	64	37	30	19.3	15.4	12.9	10.3	7.7	1.8	1.2	0.88	0.71				
	30 UC	0.52	67	39	31	20.4	16.3	13.4	11.1	8.9	6.7	1.5	1.0	0.77				
	40 UC	0.54	70	41	32	21.4	17.2	14.1	11.3	9.2	7.0	1.7	1.1	0.83				
	50 UC	0.55	72	42	33	22.4	18.1	15.1	12.1	9.1	2.1	1.4	1.0	0.83				
TTI11005 (50)	15 UC	0.56	72	42	33	22.4	18.1	15.1	12.1	9.1	2.1	1.4	1.0	0.83				
	20 UC	0.58	75	44	34	23.4	19.0	16.0	13.0	10.0	2.2	1.5	1.1	0.90				
	30 UC	0.60	77	45	35	24.4	19.9	16.9	13.9	11.0	2.3	1.6	1.2	0.97				
	40 UC	0.62	79	46	36	25.4	20.8	17.8	14.8	12.0	2.4	1.7	1.3	1.0				
	50 UC	0.63	81	47	37	26.4	21.7	18.7	15.7	13.0	2.5	1.8	1.2	0.90				
TTI11006 (50)	15 UC	0.64	82	48	38	27.4	22.6	19.6	16.6	14.0	2.6	1.9	1.3	1.0				
	20 UC	0.66	84	49	39	28.4	23.5	20.5	17.5	15.0	2.7	2.0	1.4	1.1				
	30 UC	0.68	86	50	40	29.4	24.4	21.4	18.4	16.0	2.8	2.1	1.5	1.2				
	40 UC	0.70	88	51	41	30.4	25.3	22.3	19.3	17.0	2.9	2.2	1.6	1.3				
	50 UC	0.71	89	52	42	31.4	26.2	23.2	20.2	18.0	3.0	2.3	1.7	1.4				
TTI11008 (50)	15 UC	0.72	90	53	43	32.4	27.1	24.1	21.1	19.0	3.1	2.4	1.8	1.4				
	20 UC	0.73	93	54	44	33.4	28.0	25.0	22.0	20.0	3.2	2.5	1.9	1.5				
	30 UC	0.74	95	55	45	34.4	28.9	25.9	23.0	21.0	3.3	2.6	2.0	1.6				
	40 UC	0.75	96	56	46	35.4	29.8	26.8	24.0	22.0	3.4	2.7	2.1	1.7				
	50 UC	0.76	97	57	47	36.4	30.7	27.7	25.0	23.0	3.5	2.8	2.2	1.8				
TTI11010	15 UC	0.77	101	59	47	39	29	25	21	19	3.6	2.9	2.1	1.7				
	20 UC	0.78	104	60	48	40	30	26	22	20	3.7	3.0	2.2	1.8				
	30 UC	0.79	107	61	49	41	31	27	23	21	3.8	3.1	2.3	1.9				
	40 UC	0.80	109	62	50	42	32	28	24	22	3.9	3.2	2.4	2.0				
	50 UC	0.81	111	63	51	43	33	29	25	23	4.0	3.3	2.5	2.1				

CONTACT PRODUCT	SYSTEMIC PRODUCT	DRIFT MANAGEMENT
—	EXCELLENT	EXCELLENT



Optimum Spray Height



How to order:

Specify tip number.

Example:

TTI11004-VP - Polymer with VisiFlo® color-coding

TTI11003-VP-CE - Polymer with VisiFlo color-coding, includes Quick TeeJet cap and gasket

Note: Always double check your application rates. Tabulations are based on spraying water at 70°F (21°C).

Grimes, IA **800-351-1587** • Gardner, KS **877-829-8502** • Brimfield, IL **855-778-8500**