

TeeJet



The 55295 e-ChemSaver is a solenoid actuated shutoff compatible with a wide range of TeeJet nozzle bodies with a diaphragm check valve. It can be used for end of boom nozzles as well as individual tip shutoff applications.

- Valve is normally closed and opens when solenoid is energized.
- Use with most diaphragm check valve equipped with TeeJet nozzle bodies.
- 1/4 second response time
- 2-Pin MetriPack connector molded into body for a clean, weather-tight electrical connection
- Wetted materials include stainless steel
- 100 PSI maximum spraying pressure
- Voltage (12V or 24V)
- 0.6 GPM at 5 PSI pressure drop at 100 PSI pressure drop
- Offered in 12- or 24-Volt DC version



PART NO.	VOLTAGE (DC)	FOR USE WITH TEEJET NOZZLE BODY	LIST PRICE
55295-1-12	12	QJ17560A, QJ360E, QJ200, QJ300, 24216A, 24230A, QJ39685, QJ(T)8360	\$222.91
55295-1-24	24	QJ17560A, QJ360E, QJ200, QJ300, 24216A, 24230A, QJ39685, QJ(T)8360	\$222.91
55295-2-12	12	QJ360C, QJ22187, QJ8355	\$222.91
55295-2-24	24	QJ360C, QJ22187, QJ8355	\$222.91
98552-05		2 Wire, 0.5M Metri-Pack Cable	\$18.19
98552-15		2 Wire, 1.5M Metri-Pack Cable	\$23.44
98552-30		2 Wire, 3.0M Metri-Pack Cable	\$30.52



TEXAS INDUSTRIAL REMCOR SOLENOID VALVES

1999A SERIES

Series 1999A

- Maximum Pressure: 175 PSI
- GPM: 0 - 18
- Pressure Drop: 5 PSI at 18 GPM
- Voltage: 12-Volt DC
- Standard Current Draw: 1.1 AMPs
- Valve: Normally Closed
- Diaphragm/Seat/Seals: Viton®
- 1" FPT Inlet / MPT Bypass Line; 3/4" FPT Boom Outlet
- Terminals: .25" Spade / Weather Pack Available (WP)



PART NO.	DESCRIPTION	LIST PRICE
1999A-1	Solenoid Valve	\$188.03
1999A-WP	Solenoid Valve (WP)	\$189.09
<b>REPLACEMENT PARTS</b>		
2045	Repair Kit, Old Style Viton	\$114.00
2517	Repair Kit, "A", Viton	\$85.51
2518	Repair Kit, "A", Aflas	\$123.07
2515	Coil Assembly	\$135.60

2500B SERIES

Series 2500B

- Maximum Pressure: 100 PSI
- GPM: 0 - 10
- Pressure Drop: 5 PSI at 10 GPM
- Voltage: 12-Volt DC
- Standard Current Draw: 2 AMPs
- Valve: Normally Closed
- Diaphragm/Seat/Seals: Viton®
- 3/4" FPT Inlet / MPT Bypass Line; 1/2" FPT Boom Outlet
- Terminals: .25" Spade / Weather Pack Available (WP)



PART NO.	DESCRIPTION	LIST PRICE
2500B	Solenoid Valve	\$139.23
2500B-WP	Solenoid Valve (WP)	\$140.70
<b>REPLACEMENT PARTS</b>		
2352	Repair Kit	\$48.57

2201A SERIES

Series 2201A

- Maximum Pressure: 125 PSI
- GPM: 0 - 1
- Pressure Drop: 5 PSI at 1 GPM
- Voltage: 12-Volt DC
- Standard Current Draw: 1.1 AMPs
- Valve: Normally Closed
- Diaphragm/Seat/Seals: Viton®
- 1/4" FPT Inlet / Outlet
- Terminals: .25" Spade / Weather Pack Available (WP)



PART NO.	DESCRIPTION	LIST PRICE
2201A	Solenoid Valve	\$105.29
2201A-WP	Solenoid Valve (WP)	\$108.55

2203A SERIES

Series 2203A

- Maximum Pressure: 175 PSI
- GPM: 0 - 5
- Pressure Drop: 3.5 PSI at 5 GPM
- Voltage: 12-Volt DC
- Standard Current Draw: .85 AMPs
- Valve: Normally Closed
- Diaphragm/Seat/Seals: Viton®
- 1/4" FPT Inlet / Outlet
- Terminals: .25" Spade / Weather Pack Available (WP)



PART NO.	DESCRIPTION	LIST PRICE
2203A	Solenoid Valve	\$92.34
2203A-WP	Solenoid Valve (WP)	\$94.66

2100C SERIES

Series 2100C

- Maximum Pressure: 125 PSI
- GPM: 0 - 10
- Pressure Drop: 7.5 PSI at 10 GPM
- Voltage: 12-Volt DC
- Standard Current Draw: 2 AMPs
- Valve: Normally Closed
- Diaphragm/Seat/Seals: Viton®
- 3/4" FPT Inlet / MPT Bypass Line; 1/2" FPT Boom Outlet
- Terminals: .25" Spade / Weather Pack Available (WP)



PART NO.	DESCRIPTION	LIST PRICE
2100C	Solenoid Valve	\$141.19
2100C-WP	Solenoid Valve (WP)	\$143.80
<b>REPLACEMENT PARTS</b>		
2604	Repair Kit, Viton	\$75.07

2601A SERIES

Series 2601A

- Type: Direct Operating On/Off
- Maximum Pressure: 125 PSI
- GPM: 0 - 1
- Pressure Drop: 5 PSI at 1 GPM
- Voltage: 12-Volt DC
- Standard Current Draw: 1.1 AMPs
- Valve: Normally Closed
- Diaphragm/Seat/Seals: Viton®
- 1/4" FPT Inlet / 1/4" Turn Nozzle Body Outlet
- Terminals: Weather Pack Available (WP)



PART NO.	DESCRIPTION	LIST PRICE
2601A	Solenoid Valve	\$115.30

2204A SERIES

Series 2204A

- Type: 3-Way Direct Operating
- Maximum Pressure: 55 PSI
- GPM: 0 - 5
- Pressure Drop: 5 PSI at .5 GPM
- Voltage: 12-Volt DC
- Standard Current Draw: .85 AMPs
- Valve: Bottom Normally Closed Upper Normally Open
- Diaphragm/Seat/Seals: Viton®
- 1/4" FPT Inlet / Outlet
- Terminals: .25" Spade / Weather Pack Available (WP)



PART NO.	DESCRIPTION	LIST PRICE
2204A	Solenoid Valve	\$108.71
2204A-WP	Solenoid Valve (WP)	\$110.84

CATALOG IS LIST PRICE PLEASE APPLY DISCOUNT